

**Part Number :**

<u>E</u> <u>H</u> <u>I</u> - <u>CAC</u> <u>IC01</u>				
(1)	(2)	(3)	(4)	(5)
(1) Elastic RFIDTech Co.			(4) Item : Card (Clamshell)	
(2) Frequency : HF			(5) IC Type NO. (as below)	
(3) Category : Tag				



**Description :**

The HF (13.56MHz) RFID Clamshell Card is an RFID inlay embedded in clamshell card style. This special design is convenient to carry and can be printing via offset printing or silk screen. It's available in various chips for different read range, memory size and write mode depends on the application.

**Specifications :**

- Frequency : 13.56MHz
- Material : ABS + PVC
- Dimension : 85.6 x 54 x 1.8
- Weight : 9g
- Operating Temperature : -10°C to 50°C

**Applications :**

- Access Control
- Staff identification
- Property Tracking

IC Type NO.	ISO Standard	Memory	Function	IC Type	Supplier
IC01	14443A	512 bits	R / W	Mifare Ultralight	Philips
IC02	14443A	1K bytes	R / W	Mifare S50	Philips
IC03	14443A	4K bytes	R / W	Mifare S70	Philips
IC04	15693	256 bits	R / W	Tag-it™ Pro	Texas Instrument
IC05	15693	1024 bits	R / W	ICODE 2	Philips
IC06	15693	2048 bits	R / W	Tag-it™ Plus	Texas Instrument