

# HF RFID Tag (One Time Used Wristband Tag)



## Part Number :

<u>E</u>	<u>H</u>	<u>I</u>	-	<u>OWR</u>	<u>IC01</u>
(1)	(2)	(3)		(4)	(5)
(1) Elastic RFIDTech Co.	(2) Frequency : HF	(3) Category : Tag		(4) Item : one time used wristband	(5) IC Type NO. (as below)



## Description :

The HF (13.56MHz) RFID One Time Used Wristband Tag (Transponder) is a special design for human tracking, for example used for patient and newborn baby in hospital, ticketing management in club or concert. It consist of a flexible PVC wristband and an RFID HF inlay can bind on wrist very comfortable. It's a one time used tag and could be one side printing via offset printing or silk screen.

## Specifications :

- Frequency : 13.56MHz
- Material : PVC
- Dimension / Weight : 34 x 293mm / 1.5g
- Color : Depends on request
- Storage temperature : -25°C to 85°C
- Operating Temperature : -25°C to 70°C

## Applications :

- Hospital Health Care
- Newborn baby tracking
- Access Control
- Security
- Ticketing Management

IC Type NO.	ISO Standard	Memory	Function	IC Type	Supplier
IC01	14443A	512 bits	R / W	Mifare Ultralight	Philips
IC02	14443A	1K bytes	R / W	Mifare S50	Philips
IC03	15693	256 bits	R / W	Tag-it™ Pro	Texas Instrument
IC04	15693	1024 bits	R / W	ICODE 2	Philips
IC05	15693	2048 bits	R / W	Tag-it™ Plus	Texas Instrument