

Part Number :

<u>E</u> <u>L</u> <u>I</u> - <u>CAP</u> <u>IC01</u>				
(1)	(2)	(3)	(4)	(5)
(1) Elastic RFIDTech Co.			(4) Item : Card (ISO PVC)	
(2) Frequency : LF			(5) IC Type NO. (as below)	
(3) Category : Tag				



Description :

The LF (125KHz / 134.2KHz) RFID PVC Proximity Card is an RFID inlay embedded in PVC with card style. This special design is convenient to carry and can be printing via offset printing or silk screen. It's available in various chips for different read range, memory size and write mode depends on the application.

Specifications :

- Frequency : 125KHz / 134.2KHz (depends on IC)
- Material : PVC
- Dimension : 85.6 x 54 x 0.8
- Weight : 6g
- Operating Temperature : -10°C to 50°C

Applications :

- Access Control
- Staff identification
- Property Tracking

IC Type NO.	Memory	Function	IC Type	Supplier
IC01	64 bits	R / O	EM4100	EM-Marin
IC02	64 bits	R / O	EM4102	EM-Marin
IC03	64 bits	R / O	TK4100	TK
IC04	256 bits	R / W	Hitag 2	Philips
IC05	256 bits	R / W	Hitag S256	Philips
IC06	330 bits	R / W	T5567	ATMEL
IC07	2048 bits	R / W	Hitag 1	Philips