

LF RFID Tag (ABS Keyfob Tag)



Part Number :

E L T - KEA 01 - IC01					
(1)	(2)	(3)	(4)	(5)	(6)
(1) Elastic RFIDTech Co.			(4) Item : Keyfob (ABS)		
(2) Frequency : LF			(5) Shape Type NO. (as below)		
(3) Category : Tag			(6) IC Type NO. (as below)		



Description :

The LF (125KHz / 134.2KHz) RFID ABS Keyfob Tag (Transponder) is an RFID inlay embedded in ABS housing with a keyfob style by ultrasonic plastic welding. This special design is convenient to carry as a normal keyfob with small dimension, fashion and beautiful style. It's available in various styles, chips for different read range, memory size and write mode depends on the application.

Specifications :

- Frequency : 125KHz / 134.2KHz (depends on IC)
- Material : ABS
- Dimension : As below
- Color : Blue / Red / Grey / Yellow / White / Purple
- Operating Temperature : -10°C to 50°C

Applications :

- Access Control
- Staff identification
- Property Tracking

IC Type NO.	Memory	Function	IC Type	Supplier
IC01	64 bits	R / O	EM4100	EM-Marin
IC02	64 bits	R / O	EM4102	EM-Marin
IC03	64 bits	R / O	TK4100	TK
IC04	256 bits	R / W	Hitag 2	Philips
IC05	256 bits	R / W	Hitag S256	Philips
IC06	330 bits	R / W	T5567	ATMEL
IC07	2048 bits	R / W	Hitag 1	Philips

LF RFID Tag (ABS Keyfob Tag)



KEA01 (54.8x35.3x6.2mm)



KEA02 (40.1x31.8x4.2mm)



KEA03 (55.8x37.3x8.5mm)



KEA04 (34.8x28.0x6.9mm)



KEA05 (47.4x29.4x7.2mm)



KEA06 (53x37.5x9.8mm)



KEA07 (51.4x1x32.3x5.4mm)



KEA08 (52.5x35.2x8.7mm)



KEA09 (50.3x32x7.0mm)

